

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

## Shortcuts:

<b>Ctrl + C</b>	Copy
<b>Ctrl + D</b>	Print
<b>Ctrl + E</b>	Send by eMail
<b>Ctrl + F</b>	Find
<b>Ctrl + N</b>	New note
<b>Ctrl + O</b>	Open note
<b>Ctrl + P</b>	Password-protection
<b>Ctrl + R</b>	Replace
<b>Ctrl + S</b>	Save
<b>Ctrl + T</b>	Standard-Toolbar
<b>Ctrl + U</b>	Save (with file-dialog)
<b>Ctrl + V</b>	Paste
<b>Ctrl + X</b>	Cut
<b>Ctrl + Y</b>	Remove Font-Style
<b>Ctrl + Shift + A</b>	Font-Name
<b>Ctrl + Shift + B</b>	Bold
<b>Ctrl + Shift + C</b>	Center
<b>Ctrl + Shift + F</b>	Font
<b>Ctrl + Shift + I</b>	Tabulator
<b>Ctrl + Shift + K</b>	Italic
<b>Ctrl + Shift + L</b>	Left
<b>Ctrl + Shift + P</b>	Font-Size
<b>Ctrl + Shift + R</b>	Right
<b>Ctrl + Shift + U</b>	Underline
<b>F1</b>	Show Readme
<b>F3</b>	Find next
<b>F4</b>	Insert username
<b>F5</b>	Insert current date/time
<b>F8</b>	Record clipboard
<b>ESC</b>	Close
<b>Shift + Close-Button</b>	Autosave
<b>Ctrl + Close-Button</b>	Minimize
<b>Ctrl + Outlook-Menu-Icon</b>	System-Menu
<b>Ctrl + Config/Windows-System</b>	Set Macro-Number

## Parameters:

**filename** Opens the file called *Filename*

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

<b>/T filename</b>	Opens the file as template (No space between /T and <i>Filename!</i> )
<b>/deinst</b>	Deinstalls ActiveNote
<b>/unass</b>	Removes the NOT-file-association
<b>/defaultpos</b>	Starts ActiveNote on default-position, not on user defined
<b>/readme</b>	Creates a new Readme-document
<b>/finddialog</b>	Open the "Search For Notes"-Dialog
<b>/ver</b>	Creates an idi-file called "C:\NOTEIT.VER"
<b>/AboutBox</b>	Shows only the About-Box
<b>/LLRS</b>	Starts with delay
<b>/LoadTime</b>	Shows the load-time of ActiveNote
<b>filename /TempFile [/nomodi]</b>	Delete the note after loading and set Modified=TRUE [FALSE]
<b>/StartNote [/piano]</b>	Run in "StartNote"-Mode [say nothing if start 2 <sup>nd</sup> time]
<b>[filename] /Minimized</b>	Run ActiveNote minimized
<b>filename /print</b>	Prints the note
<b>filename /printto Printer Driver Port</b>	Prints the note on <i>Printer</i>
<b>filename /readonly</b>	Set read-only-mode
<b>/?</b>	Shows a Parameter-Information dialog

## Registry-Entries:

Possible-values in brakes "[ ]"; Bold=default

### HKEY\_CURRENT\_USER\Software\pb\Note\Note It\

<b>AttachNote</b> (DWord)	Attach .NOT-file to eMails [0/1; <b>0</b> ]
<b>AutoInsertDateTime</b> (DWord)	Insert Date/Time at the top of a new note [0/1; <b>0</b> ]
<b>AutoSaveOnDeactivate</b> (DWord)	Save Note automatically when changing Application [0/1; <b>0</b> ]
<b>AutoSaveOnIdle</b> (DWord)	Autosave n seconds after last modify [0..n; <b>0</b> ]
<b>CatchCorner</b> (DWord)	Reduce the title-bar to a corner (snap edge) [0/1; <b>0</b> ]
<b>Color</b> (DWord)	Standard-Color [0..16777215; <b>8454143</b> ]
<b>ColorNr</b> (DWord)	Menu-Number of Standard-Color [0..5; <b>0</b> ]
<b>CompressMode</b> (DWord)	CompressMode of [0..2; <b>2</b> ] <sup>i</sup>
<b>ClpTxtInsert</b> (DWord)	Insert Clipbrd unformatted, if 1 [0/1; <b>0</b> ]
<b>DateFormat</b> (String)	Format String for F5 ["hh:nn dd/mm/yy"] <sup>ii</sup>
<b>Dir</b> (String)	Standard save-dirctory
<b>EnlargeTitle</b> (String)	Controls the title-style [0..4; <b>1</b> ]
<b>ExeFile</b> (String)	File and path of ActiveNote-Application
<b>ExeVer</b> (DWord)	Version of ActiveNote (*100)

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

<b>FileCount</b> (DWord)	En-/Disables the file-counting [0/1; <b>0</b> ]
<b>FileName</b> (String)	Standard Filename
<b>Footer</b> (String)	Print-Footer [“”] <sup>iii</sup>
<b>FooterFormat</b> (String)	Format of Print-Footer [“> <b>100</b> ”] <sup>iv</sup>
<b>FontCharset</b> (DWord)	Charset of Standard-Font [0..255; <b>1</b> ]
<b>FontColor</b> (DWord)	Color of Standard-Font [0..16777215; <b>0</b> ]
<b>FontHeight</b> (DWord)	Height of Standard-Font
<b>FontName</b> (String)	Name of Standard-Font
<b>FontSize</b> (DWord)	Size of Standard-Font
<b>FontStyle</b> (String)	Style of Standard-Font [“” ..“bius”; “”]
<b>Header</b> (String)	Print-Header [“”]
<b>HeaderFormat</b> (String)	Format of Print-Header [“> <b>100</b> ”]
<b>Height</b> (DWord)	Standard-height of a note (in pixel)
<b>Lang</b> (String)	Language of ActiveNote [“D”;“E”;“F”;“S”;“PT-B”;“PL”]
<b>Left</b> (DWord)	Left-Position of a note (pxl. from screen-border)
<b>MarginBottom</b> (DWord)	Bottom-print margin in Millimeters
<b>MarginLeft</b> (DWord)	Left-print margin in Millimeters
<b>MarginRight</b> (DWord)	Right-print margin in Millimeters
<b>MarginTop</b> (DWord)	Margin-print margin in Millimeters
<b>MinBlink</b> (DWord)	Let a minimized note change it's color [0/1; <b>1</b> ]
<b>NoConfig</b> (DWord)	Hides the “Config”-Menu [0/1; <b>1</b> ]
<b>NotelconIndex</b> (DWord)	Index of icon in NotelconModule-File []
<b>NotelconModule</b> (String)	Container-File for a Note's icon [“” = automatic icon]
<b>NoTxtConfirmation</b> (DWord)	Hides the TXT-Format confirmation [0/1; <b>0</b> ]
<b>Orientation</b> (DWord)	Printer-Orientation [ <b>0</b> =Portrait, <b>1</b> =Landscape]
<b>ReceptionServer</b> (String)	Last server-name, a note was sent to
<b>RestoreDelay</b> (DWord)	Delay when starting by LLRS
<b>RunStartNote</b> (DWord)	Controls the AutoStart of StartNote
<b>SenderName</b> (String)	Name of DirectSend-Sender [ <b>System-Logon-Name</b> ]
<b>SMTPAdr</b> (String)	User's personal eMail-Address
<b>SMTPMail</b> (DWord)	Use SMTP-Mail (instead of MAPI) if “1” [0/1; <b>0</b> ]
<b>SMTPName</b> (String)	User's name
<b>SMTPServer</b> (String)	The IP-Address of the SMTP-Server
<b>StayOnTop</b> (DWord)	Let the note be the topmost-window [0/1; <b>1</b> ]
<b>TCP-Port</b> (String)	DirectSend-TCP-Port [ <b>2000</b> ] (“disabled” to disable)
<b>ThinBorder</b> (DWord)	Makes a thin window-border [0/1; <b>1</b> ]
<b>ThinBorderWidth</b> (DWord)	Width of thin window-border [ <b>1</b> ]
<b>Top</b> (DWord)	Top-Position of a note (pxl. from screen-border)
<b>Width</b> (DWord)	Standard-width of a note (in pixel)

HKEY\_CURRENT\_USER\Software\pb\Note\Note It\menu

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

Controls the visibility of menu-entries; 1 = visible; 0 = not visible

<b>Break</b> (DWord)	Center bar + menu-break
<b>Datei1</b> (DWord)	Menu-captions
<b>Direktsenden1</b> (DWord)	Send note directly
<b>Drucken1</b> (DWord)	Print
<b>Farbe1</b> (DWord)	Color-Menu
<b>Favoriten1</b> (DWord)	Favorite-Menu
<b>FormatToolbar2</b> (DWord)	Toolbar-Menu ( <i>old value</i> )
<b>ImportExport1</b> (DWord)	Import/Export entry
<b>ImVordergrund1</b> (DWord)	Stay on top
<b>Laden1</b> (DWord)	Open
<b>Mitpasswortschtzen1</b> (DWord)	Password
<b>N2</b> (DWord)	Menu-Captions
<b>Neu1</b> (DWord)	New note
<b>Objekt1</b> (DWord)	Object-Menu
<b>Peremailsenden1</b> (DWord)	Send by eMail
<b>Schließen1</b> (DWord)	Close and trash
<b>Schriftart1</b> (DWord)	Font
<b>Seiteeinrichten1</b> (DWord)	Page-Setup
<b>ShowToolbar2</b> (DWord)	Toolbar-Menu ( <i>old value</i> )
<b>Speichern1</b> (DWord)	Save
<b>Speichernunter1</b> (DWord)	Save as
<b>Suchenersetzen1</b> (DWord)	Find-Menu
<b>Toolbars1</b> (DWord)	Toolbar-Menu
<b>Zwischenablage1</b> (DWord)	Clipboard-Menu

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\reception

<b>Accept#0</b> .. <b>Accept#n</b> (String)	User name 0..n, from whom notes are always accepted.
<b>AcceptNotes</b> (DWord)	Accept notes generally [0/1; 1]
<b>AcceptUnknownNotes</b> (DWord)	Accept notes from unknown senders [0/1; 1]
<b>DestDir</b> (String)	Destination-Directory [""=Desktop]
<b>OpenNotes</b> (DWord)	Open notes automatically [0/1; 1]
<b>Reject#0</b> .. <b>Reject#n</b> (String)	User name 0..n, from whom notes are always rejected.

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\saveto

<b>Bez1</b>	Caption 1..9 of the favorites.
-------------	--------------------------------

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

**.. Bez9** (*String*)  
**Dir1** Directory 1..9 of the favorites.  
**.. Dir9** (*DWord*)

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\recent

Recent-List of ActiveNote

**MaxRecent** (*DWord*) Maximal-Length of Recent-List [50]  
**{Filename#1}** (*Binary*) Filename and Count-Code  
**{Filename#n}** (*Binary*)

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\receivers

**direct#0** History of Direct Send Note  
**.. direct#n** (*String*)  
**mail#0** History of Send By Mail  
**.. mail#n** (*String*)  
**HistoryLength** (*DWord*) Maximal length of histories [20, 0 = no limit]

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\Toolbars

**ShowStatus** (*DWord*) ShowStatusBar [0/1; 0]

Controls the visibility of toolbar-buttons; 1 = visible; 0 = not visible

**Bold** (*DWord*) Bold  
**Bullets** (*DWord*) Bullets  
**CenterAlign** (*DWord*) Align = Center  
**Color** (*DWord*) Note-Color  
**Config** (*DWord*) Config-Dialog  
**Copy** (*DWord*) Copy  
**Cut** (*DWord*) Cut  
**Delete** (*DWord*) Delete  
**Find** (*DWord*) Find-Dialog  
**FindNext** (*DWord*) Find next  
**font** (*DWord*) Font-Dialog  
**FontColor** (*DWord*) Font color  
**FontName** (*DWord*) Font name

# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

<b>FontSize</b> (DWord)	Font size
<b>Info</b> (DWord)	Info-Dialog
<b>Italic</b> (DWord)	Italic
<b>LeftAlign</b> (DWord)	Align = Left
<b>New</b> (DWord)	New note
<b>Object</b> (DWord)	New Object
<b>Open</b> (DWord)	Open
<b>Password</b> (DWord)	Password-Protection
<b>Paste</b> (DWord)	Paste
<b>Print</b> (DWord)	Print
<b>Replace</b> (DWord)	Replace-Dialog
<b>RightAlign</b> (DWord)	Align = Right
<b>Save</b> (DWord)	Save
<b>saveAs</b> (DWord)	Save as
<b>SendDirekt</b> (DWord)	Send note direct
<b>SendMail</b> (DWord)	Send per eMail
<b>Time</b> (DWord)	Date/Time-Stamp
<b>Underline</b> (DWord)	Underlined

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\Toolbars\Toolbar1

<b>DockedTo</b> (String)	Toolbar-Dock ["nil";" <b>Dock1</b> ";"Dock2"; "Dock971";"Dock972"]
<b>DockPos</b> (String)	Position of Toolbar in Dock
<b>DockRow</b> (String)	Row of Toolbar in Dock
<b>FloatBottom</b> (String)	} Information about a floating toolbar
<b>FloatLeft</b> (String)	
<b>FloatRight</b> (String)	
<b>FloatRightX</b> (String)	
<b>FloatTop</b> (String)	
<b>Visible</b> (String)	Toolbar visible [0/1; 1]

## HKEY\_CURRENT\_USER\Software\pb\Note\Note It\Toolbars\Toolbar2

*Same as Toolbar1*

## HKEY\_CURRENT\_USER\Software\pb\Note\NoteMap\2.0

<b>Akt</b> (DWord)	Refresh value in Sec. [1...; 5]
--------------------	---------------------------------



# ActiveNote 4.01 Function -Sheet

This document  
is not an official one.  
No warranty for any  
of the informations.

---

ddd	Prints the day with the abbreviation (Sun - Sat) and use the strings from the global variable ShortDayNames.
dddd	Prints the full-day name (Sunday – Saturday) and use the strings from the global variable LongDayNames.
ddddd	Prints the date in the ShortDateFormat.
dddddd	Prints the day in the LongDateFormat.
m; mm; mmm; mmmm	Equal the month
yy; yyyy	Equal the year
h; hh	Equal the hour
n; nn	Equal the minute
s; ss	Equal the second
t	Prints the time in the ShortTimeFormat.
tt	Prints the time in the LongTimeFormat.
am/pm	Use the 12h-System with 'am/pm'
a/p	Use the 12h-System with 'a/p'
ampm	Use the 12h-System with 'TimeAMString/TimePMString'
/	Use the global DateSeparator.
:	Use the global TimeSeparator.
'xx'/'xx'	Write ,xx' as String without any interpretation

- iii In the code string **{ \$PAGE }** the actual page number is incorporated.  
In the code string **{ \$DATE }** the actual date is incorporated.  
In the code string **{ \$TIME }** the actual time is incorporated.  
In the code string **{ \$TITLE }** the notes title is incorporated  
In the code string **{ \$LINE }** the actual line number is incorporated.

*Examples:* Footer='Page { \$PAGE }'; Header='{ \$TITLE }';  
Footer='{ \$DATE }{| \$TIME }'; (The sign | functions as a separation sign.)

- iv The headers and footers are formatted in accordance with the recipe beneath (**HeaderFormat and FooterFormat**):

<Alignment><Width>[|<Alignment><Width>...]

<Alignment> is a single character for each column. The following values are possible: '<', '^', of '>' in order to sign respectively the left side, centre and the right side in the affected column. You can choose so many columns as you wish, but the component keeps no track of the place of the column and the available paper width.

For instance: Footer='{ \$DATE }{| \$TIME }'; FooterFormat:=<50|100>

This implies that a (virtual) column with a width of 50 mm is created in which { \$DATE } to the left (<) is being adjusted. Next at the right side of a created column with a width of 100 mm the { \$TIME } will be printed.